



STEAM GENERATOR

EVO 304

Body material

Stainless steel AISI 304 (BA)

Boiler material

Stainless steel AISI 304

(with interchangeable heating element)

Boiler volume

Mod. Det, Water, 24/7: **1,5 L** | Mod. Base: **4 L**

Water tank

Mod. Det, Water, 24/7: **3 L**

Water capacity

Mod. Base: **3 L**

Detergent tank

Mod. Det: **1 L**

Maximum output

2,45 kW

Boiler output

2,4 kW

Operating pressure

Mod. Det, Water, 24/7: **8bar**

Steam production

64 g/min | **3,8 Kg/h**

Power supply

1~ 230V - 50/60 Hz

Steam T°

8 bar: **174° C**

Detergent T°

90° C - 160° C (Mod. Det)

Power cord

5 m

Weight

16 Kg | Mod. Base: **14 Kg**

Packaging

53x40x52 cm



Mod. Det




Mod. Water



Mod. 24/7



Optional trolleys:



ARENA



ARENA PLUS



ANTARES

APPLICATIONS



Single-phase steam generator for usage in the professional sector, with a stainless-steel body, unlimited steam autonomy thanks to the automatic refilling system with an internal water tank (electromechanical water level control system inside the boiler – True Temp™). Possibility to inject detergent (or hot water) together with steam. The steam generator's front panel is equipped with an electric console with commands for a timer, a thermometer and a pressure gauge; the digital display will advise the user about the necessity to proceed with the boiler maintenance.



TOOLS



JULY 6 BAR
Steam 165°C



System tested by the
University of Verona

STEAM MOP
Steam 165°C

